


IMX12 – Types and Features

Ident. no.	Type code	Description
7580000	IMX12-DI03-1S-1NAM1R-0/24VDC	1-channel isolating switching amplifier with relay output, NAMUR-Repeater
7580004	IMX12-DI03-1S-1NAM1T-0/24VDC	1-channel isolating switching amplifier with transistor output, NAMUR-Repeater
7580008	IMX12-DI03-1S-2R-S/24VDC	1-channel isolating switching amplifier with relay output, splitter function or alarm output
7580012	IMX12-DI03-1S-2T-S/24VDC	1-channel isolating switching amplifier with transistor output, splitter function or alarm output
7580016	IMX12-DI01-2S-2R-0/24VDC	2-channel isolating switching amplifier with relay output
7580020	IMX12-DI01-2S-2T-0/24VDC	2-channel isolating switching amplifier with transistor output
7580024	IMX12-DI01-2S-2PP-0/24VDC	2-channel isolating switching amplifier with push-pull output stage
7580101	IMX12-DO01-1U-1U-0/24VDC	1-channel solenoid driver
7580105	IMX12-DO01-2U-2U-0/24VDC	2-channel solenoid driver
7580301	IMX12-AI01-1I-2IU-H0/24VDC	1-channel HART® isolating transducer with splitter function
7580305	IMX12-AI01-2I-2IU-H0/24VDC	2-channel HART® isolating transducer
7580401	IMX12-AO01-1I-1I-H0/24VDC	1-channel HART®-output analog signal isolator
7580405	IMX12-AO01-2I-2I-H0/24VDC	2-channel HART®-output analog signal isolator
7580505	IMX12-TI02-1TCURTD-1I1R-C0/24VDC	1-channel universal temperature transducer with current output and limit value
7580509	IMX12-TI02-2TCURTD-2I-C0/24VDC	2-channel universal temperature transducer with current output
7580513	IMX12-TI01-2RTDR-2I-C0/24VDC	2-channel temperature transducer with current output
7580209	IMX12-FI01-2SF-2I-C0/24VDC	2-channel frequency transducer with current output
7580205	IMX12-FI01-1SF-1I1R-C0/24VDC	1-channel frequency transducer with current output and limit value

Devices with power rail and cage clamp terminals are optionally available



Dimensions		Technical data	
Operating voltage	10...30 VDC	Suitable for use in safety circuits up to	SIL 2 acc. to IEC 61508
Dimensions	12.5 x 112 x 110 mm	Explosion protection type	[Ex ia Ga] IIC; [Ex ia Da] IIC Ex nA nC [ia Ga] IIC/IIB T4 Gc
Application areas	II (1) G, II (1) D	Ambient temperature	-25...+70 °C

- Availability/Reliability**
- Transparent cover
- High channel density**
- 4 Connection possibilities on each side
- Easily mounted**
- Power supply via optional power rail

28 subsidiaries and over 60 representations worldwide!

Your Global Automation Partner

IMX12 Interface Series




Interface Series IMX12

Interface devices are the true all-rounders in the control cabinet. They combine protecting, isolating, converting and supply tasks in the smallest space. A further major challenge are the requirements in standards. In this environment, the users expect reliability, precision and safety.

Turck sets a new standard in the field of Ex-safety-barriers and Ex-analog-signal isolators with the new IMX12 interface device series. Fast and precise signal processing in the smallest space, reliable supply of the connected instrumentation and long maintenance-free operation are the most important criteria in the selection.


The IMX12 series sets standards in many respects. The devices were developed according to the current norms and standards, and are the latest interface platform on the market. You therefore benefit from investment security and availability for a long period of time. The devices of the IMX12 series are designed for processing of switching, NAMUR, frequency, current, voltage and resistance signals.




Reliable
Turck builds on many years of experience in the field of interface technology. The IMX series combines this experience with state-of-the-art technology. We offer an excellent basis for securing your investments, also in the long term and under changed market conditions.



Global
Turck is a globally operating company, thus fulfilling requirements of international markets. We offer worldwide approvals, and thus ensure the applicability of devices in different systems.



Safe
Safety first – is a maxim at Turck . With the IMX12 series, we want to contribute to your system security. All devices have been developed and manufactured in accordance with the requirements of the IEC61508 and can be used in safety circuits up to SIL2.



Flexible
No application is similar to the other. This provides a high degree of adaptability of the instrumentation. With diverse functionality and a wide voltage range of 10 to 30 VDC, the IMX12 series is tailored to these requirements.