



CABLE LENGTH	TOLERANCE *			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER			
STRIP LENGTH	TOLERANCE *			
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	±5.0mm			
* UNILESS O	THERWISE SPECIFIED			

SOURCE DRAWING - FOR REFERENCE ONLY

1. "*"	INDICATES	CABLE	LENGTH	IN	METERS.	CONTACT	TURCK	TO	ORDER	
SPECIFIC LENGTHS.										

2. "/S90" DESIGNATES THERMOPLASTIC POLYURETHANE (TPU) CABLE.

NOTES:

В	UPDATE CABLE DIAMETER AND CONDUCTOR SIZE	RDS	04/21/14	44652
REV	DESCRIPTION	BY	DATE	ECO NO.

	RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com		
ĺ	MATERIAL		DRFT JBJ	DATE 06/05/03	DESCRIPTION VBRK 4.4-2RS	4T_*/*/SC	10
	SEE SPECIFICATIONS			SCALE 1=1.0	VBINIX 1.1 ZING	(a) (b)	
ļ		DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION NO.		REV
	FINISH	CONTACT TURCK	MILLIMETE	ER [INCH]			B
	SEE SPECIFICATIONS	FOR MORE INFORMATION					
			DO NOT SCALE	THIS DRAWING	FILE: 777001786	SHEET	1 OF 1